



PSS 4000 Diag Control UA V1.20.0

This document is the original document.

All rights to this documentation are reserved by Pilz GmbH & Co. KG. Copies may be made for the user's internal purposes. Suggestions and comments for improving this documentation will be gratefully received.

Source code from third-party manufacturers or open source software has been used for some components. The relevant licence information is available on the Internet on the Pilz homepage.

Pilz®, PIT®, PMI®, PNOZ®, Primo®, PSEN®, PSS®, PVIS®, SafetyBUS p®, SafetyEYE®, SafetyNET p®, the spirit of safety® are registered and protected trademarks of Pilz GmbH & Co. KG in some countries.



SD means Secure Digital

General

This document contains important information, which must be noted. This document also contains details of the changes made in the software tool from one version to the next.

System requirements

The software tool can be installed on a PMI 5 (not PMI v5) or PC. The following system requirements apply for the PC:

Operating system:	32- or 64-bit version of Windows 7, 8, or 10;
Processor:	Pentium 4, 2 GHz (Dual Core) or desktop equivalent: Pentium 4, 2.4 GHz
RAM:	Min. 2 GB
Available hard drive space:	Approx. 1 GB
Graphics card:	Min. 1024 x 768 pixel resolution, 65536 colours
Interfaces:	Ethernet interface
To run the PSS 4000 Diag Control:	ActiveX-enabled container such as Windows Internet Explorer or an ActiveX-enabled visualisation software; (64-bit versions of ActiveX-enabled containers in visualisation software tools are not supported)
To view the documentation:	Adobe Acrobat Reader, from Version 7.1.0

Languages

This version is available in the following languages:

- German
- English

Important information

Compatibility

The PSS 4000 Diag Control UA receives data from the PSS 4000 OPC Server UA. The PSS 4000 OPC Server UA is a system section of the PSS 4000 firmware. As a result, only versions of the PSS 4000 Diag Control UA and PSS 4000 firmware that are compatible can be used simultaneously.

The PSS 4000 Diag Control UA is compatible with the following versions of the PSS 4000 firmware:

1.15.x ... 1.20.x

html file for Windows Internet Explorer

Use the latest html file when upgrading to a new version of the PSS 4000 Diag Control.

Modifications in Version 1.20.0

Modifications have no effect on the function

Changes in Version 1.19.0

Modifications have no effect on the function

Changes in Version 1.18.0

New function

► Windows 10

The use of PSS 4000 Diag Control under Windows 10 is supported.

► Diagnostic log display

If the following keys are pressed for longer than one second, automatic navigation (scrolling through the diagnostic log) starts:

- with QVGA: Cursor up, cursor down, F3 and F4
- With VGA: F3 and F4

Changes in Version 1.17.0

New function

The diagnostic log can be exported as a csv file. The export can be triggered manually on the "Diagnostic log" page and/or the file can be exported daily at a configured time.

Optimisations

► Change of certificate following an update on a PC

When the PSS 4000 Diag Control UA was updated using the installer "Software PSS 4000 Diag Control", the certificates for authenticating the PSS 4000 Diag Control UA were recreated. This no longer happens. The existing certificates are no longer overwritten.

(31880)

Changes in Version 1.16.0

New function

The following information is now also displayed in the information window, on the **Integrity** tab:

- Online check sum "Application parameters of the FS project"
- Online check sum "FS project without application parameters"

Changes in Version 1.15.0

Version 1.15.0 is the first version of the PSS 4000 Diag Control UA.

► Support

Technical support is available from Pilz round the clock.

Americas

Brazil

+55 11 97569-2804

Canada

+1 888 315 7459

Mexico

+52 55 5572 1300

USA (toll-free)

+1 877-PILZUSA (745-9872)

Asia

China

+86 21 60880878-216

Japan

+81 45 471-2281

South Korea

+82 31 778 3300

Australia

+61 3 95600621

Europe

Austria

+43 1 7986263-0

Belgium, Luxembourg

+32 9 3217570

France

+33 3 88104003

Germany

+49 711 3409-444

Ireland

+353 21 4804983

Italy, Malta

+39 0362 1826711

Scandinavia

+45 74436332

Spain

+34 938497433

Switzerland

+41 62 88979-32

The Netherlands

+31 347 320477

Turkey

+90 216 5775552

United Kingdom

+44 1536 462203

**You can reach our
international hotline on:**

+49 711 3409-444

support@pilz.com

Pilz develops environmentally-friendly products using ecological materials and energy-saving technologies. Offices and production facilities are ecologically designed, environmentally-aware and energy-saving. So Pilz offers sustainability, plus the security of using energy-efficient products and environmentally-friendly solutions.



We are represented internationally. Please refer to our homepage www.pilz.com for further details or contact our headquarters.

Headquarters: Pilz GmbH & Co. KG, Felix-Wankel-Straße 2, 73760 Ostfildern, Germany
Telephone: +49 711 3409-0, Telefax: +49 711 3409-133, E-Mail: info@pilz.com, Internet: www.pilz.com

PILZ
THE SPIRIT OF SAFETY

CEC® CHRE®, CMSE®, InduraNET p®, Leansafe®, Master of Safety®, PAS4000®, PAScal®, PASconfig®, Pilz®, PIR®, PLID®, PMCPirimo®, PMCPiritego®, PMCTendo®, PMD®, PMJ®, PNOZ®, PRET®, PRCM®, PRIMO®, PRISM®, PSEN®, PSS®, PVS®, SafetyBUS p®, SafetyNET p®, THE SPIRIT OF SAFETY® are registered and protected trademarks of Pilz GmbH & Co. KG in some countries. We would point out that product features may vary from the details stated in this document, depending on the status at the time of publication and the scope of the equipment. We accept no responsibility for the validity, accuracy and entirety of the text and graphics presented in this information. Please contact our Technical Support if you have any questions.

1004325-EN-06, 2019-06 Printed in Germany
© Pilz GmbH & Co. KG, 2019