

PIT esc1 safe contact block 1 n/c

400315



PITestop, contact block, 1 N/C with monitoring, terminal (screw type).

Technical details

General data

Approval:	CE, TÜV, EAC (Eurasian)
Self-monitored:	ja

Technical data

Electrical data

Min. contact current:	1
-----------------------	---

Emergency stop

Switch cap. E-STOP to standard:	EN 60947-5-1
Contact material E-STOP:	AgNi

Relay outputs

Utilisation cat. AC15/DC13sta.:	EN 60947-5-1
Voltage AC15 safety cont.:	250
Max. current AC15 safety cont.:	3
Voltage DC13 safety cont.:	24
Contact material:	AgNi

Environmental data

Ambient temperature:	-30, 70
Pollution degree clear.&creep.:	3

Mechanical data

Mounting position:	any
--------------------	-----

Connection terminal:	Screw terminal
Height dimension:	43
Width dimension:	36
Depth dimension:	7
Net weight:	24
Gross weight:	26
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	no
REACH compliance:	Contains no SVHC substances
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
Harmonized System Code:	85365080
UNSPSC 25:	39122216
EAN-Code:	4046548043617
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27371302
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000017
ETIM Reference Feature:	EC000041
Volume:	0.027