

PSEN cs6.2p/PSEN cs6.1 1unit

542200



RFID safety switch, 2 safe SC outputs, 8-pin M8 male connector, IP67, 4 actuation directions, typ. operating distance (square) 11 mm, $S_{ao} = 8$ mm, $S_{ar} = 20$ mm, PU = 1 piece uniquely fully coded switch with actuator.

Technical details

General data	
Approval:	CE, UKCA, cULus Listed, FCC, IC, TÜV, ECOLAB, EAC (Eurasian)
Sensor principle:	Transponder
Coding level to ISO 14119:	hoch
Classification to EN 60947-5-3:	PDDB
Transponder coding:	unicat
Suitable for series connection:	ja
unit type:	Unit
Technical data	
Electrical data	
Supply voltage (V):	24
Type of supply voltage U1:	DC
Power consumption DC:	1
Inputs	
Number of inputs:	2
DC voltage at input:	24 V DC
Semiconductor outputs	
Number of OSSD outputs:	2
Number of sig. outputs:	1
Potential isolation S/C O:	nein

S/C output short circuit proof:	ja
Utilisation cat. to EN 60947-1:	DC-12
Environmental data	
Ambient temperature standard:	EN 60068-2-14
Ambient temperature:	-25
Max. ambient temp. at Hmax:	+60 °C
Max. ambient temp. at 2000 m:	+70 °C
Storage temperature standard:	EN 60068-2-1/-2
Climatic suitability standard:	EN 60068-2-30
Humidity rating:	93 % r. F. bei 40 °C
Perm. operating height ASL:	4000 m
EMC to standard ...:	EN 60947-5-3
Vibration to standard ...:	EN 60947-5-2
Acc. shock to standard1:	30g
Overvoltage category:	III
Pollution degree clear.&creep.:	3
Protection type, housing:	IP66, IP67
Switching distances	
Change op. dist. temp.change:	+0,02mm/°C
Mechanical data	
Type 1 actuator:	PSEN cs6.1
Sensor can be flush-mounted:	Ja, Montagehinweis beachten
Connection type:	M8, 8-pin male
Product material:	PBT, PA+GF, Polycarbonat
Height dimension:	26.4
Width dimension:	97.59999999999999
Depth dimension:	13
Net weight:	58
Gross weight:	75

Transponder	
Operating frequency:	122 kHz - 128 kHz
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	7c I
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead oxide
%-part of the pollutant:	> 0,1%
CAS No.:	1317-36-8
WEEE classification (08/2018):	5 devices (feed size < 50cm)
SCIP entry available:	0
Commercial data	
Harmonized System Code:	85365019
UNSPSC 25:	39122205
EAN-Code:	4046548077377
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27274601
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC002592
Volume:	0 dm3

Optional accessories



533150

PSEN cable M8-8sf, 2m



540138

SDD ES PROFINET




535111

PSEN ix2 F4 code



540337

PSEN Y junction M8-M12/M12 PIGTAIL



535112

PSEN ix2 F8 code



540310

PSEN screw M4x16 10pcs



533157

PSEN cable M8-8sf M8-8sm, 2m



533156

PSEN cable M8-8sf M8-8sm, 1m



532111

PSEN mag/cs bracket straight



532110

PSEN Winkel / bracket



533155

PSEN cable M8-8sf M8-sm, 0.5m



533154

PSEN cable M8-8sf, 30m



540317

PSEN Y junction M8 SENSOR



540329

PSEN converter M8-8sf -- M12-8sm



533153

PSEN cable M8-8sf, 20m



540318

PSEN Y junction M8 cable channel




533152

PSEN cable M8-8sf, 10m



533151

PSEN cable M8-8sf, 5m



540309

PSEN screw M4x12 10pcs

532109

PSEN cs bracket stop sliding door



532108

PSEN cs bracket stop swinging door



540130

SDD ES ETH

